

10.2.1 ALUMINIUM - DUCT TAPE 337

Soft aluminum duct tape for the sealing of pipes and air ducts

- Single-sided self-adhesive with protective film
- Very soft and easy to mould
- Easy to roll up
- Looks similar to air duct pipes



Art.-Nr.	Material	Breadth mm	Colour	Roll length/m	VPE Rolls	Weight kg / Roll
S0337/050	Aluminium	50	alu	50	24	0,450
S0337/075	Aluminium	75	alu	50	16	0,660
S0337/100	Aluminium	100	alu	50	12	0,992

Application range:

- Provides sealing for pipe connections
- For all applications where a good form fitting becomes necessary

Technical specifications:

Beam:	Aluminium
Adhesive:	Acrylic
Protective paper:	Silicone paper
Thickness:	0.06 mm ± 0.02
Total thickness:	0.06 ± 0.02 mm
Tensile strength:	12.0 N/cm
Strain:	5%
Adhesive strength on steel:	4.0 N/cm
Rolling resistance:	4.5 N/cm
Rate of burning:	Class 1 as per BS 476-part 6 Class 0 as per British Building Regulation
UL clearance:	Flame range = 5 as per UL 723 Smoke emission = 0
Operating temperature:	- 20°C till +110°C

Tips:

- Store in dry and dust free original packing - recommended storage temperature +10°C till +25°C
- Storage time 12 months after dispatch
- Increased temperature, higher humidity and direct solar radiation reduces the stability of the product during storage